



High Density Polyethylene Pipe & Fittings



PRODUCT DESCRIPTION

Sizes: 4" - 60" Solid or Perforated
 ≤ 24" available with sock
 ≥ 30" wrap in geotextile

Lengths: 20 ft. (other lengths optional)

Joints: Plain—Split or Snap Coupler
 Premium—Gasketed Bell/Spigot Connection

Fittings: Tee, Wye, 90's, 45's, 22's, etc.
 UGDS Fittings with Access Risers

Manufactured in accordance with AASHTO M-294 and AASHTO M-252

FEATURES & BENEFITS

- ◆ EPA recognized "Infiltration BMP" when system is perforated. 82-95% TSS removal rate when system is perforated. (EPA)
- ◆ Lightweight and easy to install
- ◆ High strength
- ◆ Easy to maintain (flush system and vacuum system clean)
- ◆ Capable of being installed in a H-20 loaded condition or in a greenbelt
- ◆ Custom fittings available
- ◆ Reduces joints by 60% over concrete storm sewer systems.

- ◆ High chemical and abrasion resistance
- ◆ High impact resistance
- ◆ Install using trench spec of ASTM D2321
- ◆ Excellent soil pipe interaction

<u>Class I</u>	<u>Class II</u>	<u>Class III</u>
Stone	Gravel	Sand
no comp	80% MP	95% MP

Kennedy Solutions, Inc.
 800-699-4046

Contact us at sales@kennedysolutionsinc.com