



# High Density Polyethylene Pipe & Fittings



## PRODUCT DESCRIPTION

Sizes: 4" - 60"      Solid or Perforated  
   ≤ 24" available with sock  
   ≥ 30" wrap in geotextile

Lengths: 20 ft. (other lengths optional)

Joints: Plain—Split or Snap Coupler  
             Premium—Gasketed Bell/Spigot Connection

Fittings: Tee, Wye, 90's, 45's, 22's, etc.  
             UGDS Fittings with Access Risers

Manufactured in accordance with AASHTO M-294 and AASHTO M-252

## FEATURES & BENEFITS

- ◆ EPA recognized "Infiltration BMP" when system is perforated. 82-95% TSS removal rate when system is perforated. (EPA)
- ◆ Lightweight and easy to install
- ◆ High strength
- ◆ Easy to maintain (flush system and vacuum system clean)
- ◆ Capable of being installed in a H-20 loaded condition or in a greenbelt
- ◆ Custom fittings available
- ◆ Reduces joints by 60% over concrete storm sewer systems.

- ◆ High chemical and abrasion resistance
- ◆ High impact resistance
- ◆ Install using trench spec of ASTM D2321
- ◆ Excellent soil pipe interaction

Class I	Class II	Class III
Stone no comp	Gravel 80% MP	Sand 95% MP

Kennedy Solutions, Inc.  
517-225-8338

Contact us at [sales@kennedysolutionsinc.com](mailto:sales@kennedysolutionsinc.com)

